



## HYCON Hydraulic Breaker HH23

Technical Data	20/30 l.p.m.
Weight, kg	23.4/23.5
Oil flow, l.p.m.	20/30
Working pressure, bar	120/120
Max. pressure, bar	160/160
Blow frequency, 1/min.	1380/1380
Noise level 1 m $L_{PA}$ dB	96/96
Noise level $L_{WA}$ dB	108/108
Vibration level, $m/s^2$	4.7/4.7
Tool size, mm hex	25x108/25x108

### HYCON FACTS MEDIUM WEIGHT ALLROUND BREAKER

HYCON HH23 is a compact and sturdy breaker with 40% higher performance than HH20.

It is designed for tough jobs in strong concrete, asphalt, ramming, etc.

Comes standard with the HYCON PROLINE vibration-reduced handle, which efficiently ensures high operator comfort. HH23 is available both as 20 and 30 l.p.m. models. HH23 is especially used by contractors, armies, asphalt companies, municipalities etc. and is very suitable for the rental business.

Std. tool size is hex 25x108 mm.

The breaker can be connected to the HPP-series (see the backpage) and other hydraulic power sources.

Other tool sizes on request.



## HYCON Hydraulic Breaker HH25

Technical Data	20/30 l.p.m.
Weight, kg	25.3/25.8
Oil flow, l.p.m.	20/30
Working pressure, bar	120/120
Max. pressure, bar	160/160
Blow frequency, 1/min.	1380/1380
Noise level 1 m $L_{PA}$ dB	96/96
Noise level $L_{WA}$ dB	108/108
Vibration level, $m/s^2$	5.5/5.5
Tool size, mm hex	32x160/32x160

### HYCON FACTS MEDIUM WEIGHT ALLROUND BREAKER

HYCON HH25 is compact and has very high performance in relation to its weight.

It is designed for tough jobs of breaking strong concrete, asphalt, frozen ground, ramming jobs, etc.

HH25 comes standard with the HYCON PROLINE vibration-reduced handle. It is available both as 20 and 30 l.p.m. versions. It is especially used by contractors, armies, asphalt companies, supply companies, rental etc.

Std. tool size is hex 32x160 mm.

The breaker can be connected to the HPP-series (see the backpage) and other hydraulic power sources.

Other tool sizes on request.



## HYCON Hydraulic Breaker HH27

Technical Data	20/30 l.p.m.
Weight, kg	27.4/27.4
Oil flow, l.p.m.	20/30
Working pressure, bar	130/130
Max. pressure, bar	160/160
Blow frequency, 1/min.	1260/1260
Noise level 1 m $L_{PA}$ dB	97/97
Noise level $L_{WA}$ dB	109/109
Vibration level, $m/s^2$	6.3/6.3
Tool size, mm hex	32x160/32x160

### HYCON FACTS HEAVY DUTY BREAKER

HYCON HH27 is exceptionally strong coping with all jobs requiring extreme power (75% higher performance than HH20). Best power to weight ratio.

It is designed for breaking hard concrete, asphalt, ramming jobs etc.

HH27 comes standard with the HYCON PROLINE vibration-reduced handle. It is especially used by contractors, armies, rail roads etc.

Std. tool size is hex 32x160 mm.

The breaker can be connected to the HPP-series (see connection table on the backpage) and other hydraulic power sources.

Other tool sizes on request.

